



# **Organic Deposit Control Products**

#### BSC<sup>™</sup> 8000

Buckman System Clean (BSC<sup>™</sup>) 8000 is a specially designed, concentrated, cleaning dispersant for use in cooling water systems. BSC 8000 contains a unique combination of active ingredients consisting of an amine, an amide, and a nonionic surfactant. BSC 8000 is especially effective in cleaning organic deposits. BSC 8000 functions by chemically working into the deposit matrix and loosening the deposit. The chemical action of BSC 8000 results in the dispersal and sloughing off of the matrix. Consistent use of BSC 8000 will help control deposition and under-deposit corrosion. BSC 8000 will also aid in the cleaning of heavily fouled systems.

#### **BSC 8007**

BSC 8007 is a specially designed cleaning dispersant for use in cooling water systems. BSC 8007 contains a unique formulation that is especially effective in cleaning organic deposits. Because organics often act as adhesives for inorganic foulants, BSC 8007 is also useful as an adjunct to mineral scale control agents.

BSC 8007 penetrates and forms a protective film as it disperses the deposits. This dual action makes it the most effective corrosion inhibitor available for control of microbiologically induced corrosion. Unlike many dispersants, BSC 8007 is compatible with glutaraldehyde and has the added benefit of controlling foam in many situations.

#### BSC 8020

BSC 8020 is a combination of cleaners for use in cooling water systems. BSC 8020 contains a unique combination of an amide and a cationic polymer. BSC 8020 is especially effective in preventing organic deposits.

BSC 8020 functions by chemically working into the deposit matrix and loosening the deposit. The chemical action of BSC 8020 results in the dispersal and sloughing off of the matrix. Consistent use of BSC 8020 will help control deposition and under-deposit corrosion. BSC 8020 will also aid in the cleaning of heavily fouled systems.

### **DMATO**

DMATO is a unique chemical amide which has properties that make it useful in both cooling and boiler water systems as a penetrant, dispersant, and corrosion inhibitor. DMATO also functions as an emulsion breaker in fluids containing a high percentage of water in various waste oils.

# Inorganic Deposit Control Products

# Bulab<sup>™</sup> 8210

Bulab 8210 is an on-line neutral cleaner for closed loop water systems. It is formulated to both clean and passivate the system. The unique formula is a blend of sequestrants and dispersants designed to facilitate the removal of iron and calcium hardness deposits. Fed at the recommended doses, Bulab 8210 will not affect system pH. A yellow metal inhibitor is also incorporated to protect copper in the system.

### Busolve FE2 and Busolve FE3

Busolve FE products are a proprietary blend of high performance iron sequestrants and surfactants. Offered in the two packages: FE2 at 24%, and FE3 at 48% active ingredients. The Busolve FE products are

specifically designed and optimized for iron control along with remediation of iron-based deposits. Applications include preventing iron deposits and "black water" in salt water disposal wells (SWD), flowlines, pipeline transmission lines, and oilfield production wells. The blends have demonstrated elevated performance at lower dosages compared to currently offered products on the market.

## CHEL

CHEL is a water-soluble blend of chelating and scale control agents designed to efficiently remove existing corrosion products and inorganic scale. Stable when temperatures, pressures, and pH values are extreme, CHEL is ideal for cleaning systems that cannot be taken offline due to workload, or for systems where acid cleaning is not an option.

Figure 1. A heat exchanger fouled

with a calcium and iron based scale after acid cleaning

Figure 2. The results indicate efficient scale removal after just one month of CHEL treatment.

Created as a combination product, CHEL contains ingredients that target removal of both iron and calcium scale, and provides the additional benefit

of acting as a sequestrant for manganese, copper, and other problematic metal ions. CHEL was formulated to work in both open and closed systems, and can be used as a scale inhibitor and antiprecipitation agent once the scale has been removed.

# **Specialty Products**

# SADA 2

SADA 2 is a combination of dispersing agents and scale inhibitors. The product is broad spectrum and is used to remove old deposits of scale, mud, oil, slime, and other fouling materials and to prevent the formation of new non-microbiological deposits. SADA 2 is recommended for use in boilers, cooling water systems, air washers, petroleum secondary recovery systems, and other industrial water systems.

SADA 2 can also be used to supplement corrosion protection to cooling water systems, boilers, and other water systems. Since part of ` the product will steam distill, it should also help protect condensate return lines from corrosion when it is used in boiler water treatment.

# DEVIS

DEVIS is a cleaner that dissolves oil-based residues. DEVIS is a ready-to-use fuel oil conditioner formulated to treat problems associated with the transport, storage, and combustion of residual fuels.

Treatment of fuel oils with DEVIS provides better dispersion of heavy hydrocarbons, carbon, water, and other sludge- and deposit-forming substances. Treatment improves atomization and combustion of the fuel oils. It also decreases corrosion of metal equipment that comes in contact with the fuel oil.


Some of the benefits derived from the use of this product include reduced buildup of tank-bottom sludge, minimal varnish and gum formation, and cleaner lines, strainers, preheaters, orifices, and burners. Fewer deposits in the furnace and less soot formation improve the overall furnace efficiency.

This is not an offer for sale. The product shown in this literature may not be available for sale and/or available in all geographies where Buckman is represented. The claims made may not have been approved for use in all countries. Buckman assumes no obligation or liability for the information. Please contact your Buckman sales representative for more information

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including **NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE.** No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty.
E525H (04/24)

Global Headquarters at 1256 N. McLean Blvd., Memphis, TN 38108, USA





Iron bolts cleaned with Bulab 8210 solution

Before

cleaning

After

cleaning

20%

30%

Argentina +54 11 4701-6415; Australia +61 (2) 6923 5888; Belgium +32 9 257 92 11; Brasil +55 (19) 3864-5000; Canada +1 (877) 282-5626; Chile +(56-2) 2946-1000; China +(86-21) 6921-0188 India + (91) 44-2648 0220; Indonesia + (62) 21-2988 8288; Korea + (82) 31-416 8991; Mexico + 52 (777) 329 3740; Singapore + (65) 6891 9200; South Africa + 27 (31) 736 8800; United States + 1 (901) 278-0330